


AI Accelerator& GPU Preliminary

MXM Module MX2000B-VA



Features


- NVIDIA® RTX PRO™ 2000 Blackwell Embedded GPU
- 3328 CUDA cores, 26 RT cores and 104 Tensor cores, 8GB GDDR7 memory
- PCIe Gen 4 x8 interface via golden finger
- 13.78 TFLOPS peak FP32 performance

Specifications

Model Number	MX2000B-VA	
GPU Engine Specs	NVIDIA RTX PRO 2000 Blackwell Embedded GPU Architecture: NVIDIA Blackwell CUDA Cores: 3328 Tensor Cores: 104 RT Cores: 26 Floating Point Performance: 11.03 TFLOPS Core Clock (MHz): Base= 952 / Boost= 1657	NVIDIA RTX PRO 2000 Blackwell Embedded GPU Architecture: NVIDIA Blackwell CUDA Cores: 3328 Tensor Cores: 104 RT Cores: 26 Floating Point Performance: 13.78 TFLOPS Core Clock (MHz): Base= 1522 / Boost= 2070
Memory Specs	Size: 8GB GDDR7 Speed: 24 Gbps Interface Width: 128-bit Bandwidth (GB/sec): 384	
Feature Support	PCI Express 4.0 x8 DirectX: 12 Ultimate Open GL 4.6 Vulkan 1.2	
Display	Resolution: 7680x4320 ¹ Maximum resolution 8K@60Hz (7690x4320) Max: 3x DisplayPort 2.1a (DSC1.2a)	
Power Consumption	Total Graphics Power (TGP): 45 W @PWR_SRC 19V	Total Graphics Power (TGP): 60 W @PWR_SRC 19V
Form Factor	MXM Graphics Module Version 3.1, Type A	
Dimensions (WxD)	82.0 x 70.0 mm (3.22" x2.75")	
Net Weight	0.037 kg (0.082 lb) (T.B.D.)	
Temperature	Standard: Operating Temp.: 0 to + 55°C (32°F ~131°F) / Extended Operating Temp.: -40 to + 85°C (-40°F ~185°F) (T.B.D.)/ Storage Temperature: -40 to + 85°C (- 40°F ~ 185°F)	
Humidity	40°C @ 95%, Non-condensing	
OS Support	Windows 10-64bit / Windows 11 / Linux 64-bit	
Certification	CE/FCC/UKCA	

1. Up to 4k 12-bit HDR at 240Hz with DP1.4a+DSC. Up to 8k 12-bit HDR at 60Hz with DP 1.4a+DSC or HDMI2.0+DSC. With dual DP1.4a+DSC, up to 8K HDR at 120Hz. HDCP 1.2/1.4. (eDP, LVDS, VGA, USB-C display output are not supported)

System & Mounting Dimensions



Product Specifications are subject to change without prior notice

Ordering Information

Model name	Description
MX2000B-VAA-A1	MXM-A, NVIDIA RTX PRO 2000 Blackwell, Gen4.0 x8, 8GB GDDR7, 3xDP, 60W, 0°C to +55°C
MX2000B-VAA-A2 (T.B.D.)	MXM-A, NVIDIA RTX PRO 2000 Blackwell, Gen4.0 x8, 8GB GDDR7, 3xDP, 45W, 0°C to +55°C

Accessory (Optional)

Part No.	Description
92-6MXM4H-1002	PCIe Carrier Board, MXM3.1, Gen4.0 x16, 4x HDMI, 0°C to +55°C
TBD	MXM-A Cooler, TWO BALL, 12V 4PIN